

Unattended ground sensors standards working group

Robert Heathcock^a, Kent Linnebur^b, Colson Brasch^b

^aDefense Intelligence Agency, Bldg 6000, 200 MacDill Blvd, Bolling AFB,
Washington, DC, USA 20340-5100;

^bThe MITRE Corporation, 7515 Colshire Drive, McLean, VA, USA 22102-7539

ABSTRACT

The Department of Defense has established an Unattended Ground Sensor (UGS) Standards Working Group to address the interoperability of UGS, promote competition, provide enhanced capabilities, and support UGS missions.

Keywords: UGS, interoperability, Sensor Web Enablement, standardization, plug-and-play

1. INTRODUCTION

The Deputy Under Secretary of Defense for Technical Collection and Analysis has emphasized the critical importance of standards to unattended ground sensors (UGS) by establishing an UGS Standards Working Group¹. This working group will identify and define interface standards for present and future UGS systems. It will also help the Defense Intelligence Agency (DIA) develop a robust set of UGS standards and interfaces tailored to user requirements. This clearly defined set of standards and interfaces will improve UGS interoperability, manufacturability, and reproducibility. These improvements will subsequently enhance competition, benefiting both the government and commercial vendors.

UGS standardization offers several key benefits. For example, standardization enables interoperability across sensors, aids sensor discovery, eases sensor development, provides a consistent baseline for data quality comparisons, and optimizes sharing of data products.

The most critical standards are interface standards, which lay the foundation for a plug-and-play capability. Plug-and-play facilitates automated discovery of UGS in a region of interest as sensors are sequentially emplaced². Without this automated discovery, emplaced sensors cannot exchange data in a timely manner, if at all.

A UGS controller with plug-and-play capability depends upon well-defined internal data standards. However, defined standards must apply in layered fashion to the controller, the UGS themselves, and the network external to the UGS. Only then can UGS standardization ensure backwards compatibility with previously fielded variants. Supporting previously fielded variants as standalone systems quickly becomes cumbersome and expensive.

Robust UGS internal and external standards that apply to legacy, current, and future UGS systems span time. However, these standards must also span sensor phenomenologies, such as magnetic, acoustic, visible, and infrared (IR). In addition, they must take into account various emplacement concepts, which help determine the different ruggedized connectors needed to ensure persistent surveillance at a specific location. Finally, robust UGS standards must allow for a broad spectrum of interface technologies. For example, UGS power source flexibility can drive interface standards in battery applications, direct connects, radio frequency (RF) energy harvesting, and photovoltaic solar cells.

2. OPERATIONAL REQUIREMENTS

2.1 Joint Operations

Applying advanced technologies on today's battlefield highlights the need for the military services and our coalition partners to perform their missions synergistically. Effective joint operations require that each entity share information to ensure mission success and prevent mission failure. Our forces increasingly depend upon UGS technology to achieve, improve, and share battlefield situational awareness. If our UGS systems are not interoperable, they cannot effectively discern and report situational awareness over a broad area. With incomplete information and limited situational awareness, the probability of joint mission success quickly diminishes.

2.2 Environmental Conditions

UGS systems must operate in harsh environmental conditions. Emplacement locations can vary among underground, underwater, and even above ground--on a pole, for example. The sensor and power source must endure extreme weather conditions and still operate effectively. Environmental conditions levy significant requirements on the sensor case design and interface connections to power and control devices, both internal and external. In turn, these requirements drive interface standards.

2.3 Mission Dynamics

Remote and direct control. UGS systems increasingly provide persistent surveillance of an area of interest. During sensor emplacement, the operator may not have adequate time to calibrate various sensor types and ensure proper installation and setup. The dynamic nature of the emplacement process thus calls for unique performance features, which in turn define specific interface requirements. By standardizing these interfaces, the operators can train on one system and more quickly adapt to other variants or systems. Again with sensor emplacement in mind, an operator needs direct connectivity between an UGS controller and sensor during installation to verify the health and status of the sensor. This direct interface could entail bluetooth, USB, or other serial connection protocols. The data provided over this interface must be available in both direct connect and remote control operations.

Mission duration, emplacement, and configurability. As mission requirements vary, power requirements will vary accordingly. An operator may configure a UGS system using commercial power, battery power, or solar cells. Modifying operational concepts may extend the operational life of the sensor by using different power-cycling options. For example, chaining battery cells, including a sleep mode, or timing out power-intensive operations could extend battery life, sensor operation, and mission duration. However, these power-cycling options depend upon the ability to connect the power system to the UGS via standardized connector interfaces.

3. INTEROPERABILITY

3.1 Data Content and Quality

Standard formats. A common complaint within the UGS user community concerns the incompatibility among systems developed by different vendors³. In fact, no controlling authority dictates that different generations of sensors from the same vendor be fully compatible. To date, the defense acquisition community has not standardized the data products from any class of unattended ground sensors to ensure that subsequent generations of that sensor class provide backwards compatibility. Any UGS controlling authority must consider the life cycle of the sensors, the ground controllers, and the analytic tools used to exploit the sensor data. Only then can data collected and shared across multiple systems effectively contribute to successful operations in a multi-force environment. Today's operating environment in which devices are heterogeneous and increasingly superseded requires standardized data formats that are both interoperable and extensible.

Ideally, a user would process data from one acoustic sensor and use that information cooperatively with acoustic data potentially collected by another vendor's system. Different variants of acoustic sensors may perform differently, but the data formats need not be non-standard.

Sensor status information. No controlling authority today compels vendors to develop non-unique data formats for different versions and generations of UGS systems, thus allowing unique data formats for health and status information. However, commercial vendors can feasibly develop data formats that are standard, but flexible enough to meet the warfighter's needs. A user could then interface/read data from multiple sensors without loading unique software with each upgrade of the sensor network. This flexibility would allow a UGS controller to discover network sensors in an ad hoc fashion, greatly improving operational utility and overall mission effectiveness.

3.2 Technology Transition

Plan for the next generation. A long view of the UGS life cycle merits special consideration. For instance, if an operator can leverage standard interfaces to upgrade a sensor without replacing numerous chassis, power, and communications components, then he or she can improve sensor performance while minimizing cost and schedule impacts. Standardized plug-and-play hardware and software interfaces will allow the operator to increase performance as detector technologies improve. Further, they will speed reconfiguration of the sensor platform to satisfy unique missions in hostile environments, thus vastly improving UGS utility to the warfighter while minimizing personnel risks.

4. INTERFACE TECHNOLOGIES

UGS system interfaces form three basic groups: hardware, software, and communications. Only coherent standardization within each of these groups will enable seamless interoperability among different sensor systems.

4.1 Hardware

The hardware interfaces cover the mechanical and electrical connections between components of an UGS and any external devices. Harsh environmental conditions, anti-tamper features, and concealment goals often drive UGS requirements, complexity, and costs.

Mechanical requirements. Environmental operating conditions largely determine mechanical interface designs. For example, severe emplacement methodologies, such as aircraft egress, underground burial, or littoral deployment, can govern sturdier, and more expensive, mechanical interfaces. Hostile desert environments of blowing sand, ineffective software tools, and limited time drive interface costs while making the UGS physical set-up and connection processes demanding and unforgiving.

Electrical requirements. Without clear standards, vendors can design UGS system components to unique requirements without uniform power, test, or control interfaces. Standardized electrical interfaces improve manufacturability, shrink the logistics tail, lighten field employment burdens, and reduce costs. Further, standard keyed connectors boost system safety while ensuring UGS environmental integrity.

4.2 Software

Control and health. Automated discovery of UGS systems in a local network only occurs with standardization of recognize-and-respond messages that a system processes. The scientific and engineering test instruments community uses a similar approach with its IEEE-488 protocols, illustrating the benefits of standardization⁴. In like manner, by following a standard protocol, a robust UGS controller suite could handle multiple sensors and still keep pace as new systems and new users come online. Establishing the standard protocols by which UGS systems are developed constitutes the critical first step.

Data. Merging data products from disparate sensors dramatically improves the effectiveness of tactical UGS systems⁵. Using innovative data fusion techniques to correlate dissimilar data saves time and money when compared to stovepiped data exploitation systems. Smartly abstracting dissimilar data in the processing chain can aid the data fusion target ID system by hiding the data implementation details⁶. Data abstraction works best, however, with clearly defined data types.

Security and encryption. An astute enemy can intercept unencrypted communication as video information is transmitted⁷. Passing information in an open format encompasses several advantages, such as commercial exploitation software and reduced processing requirements. With deployed UGS numbers increasing, however, maintaining this open format may eventually compromise operational security and data integrity⁸.

4.3 Communications

Direct connect. During UGS emplacement, an operator must ensure proper operation prior to departure. Using a test port, the operator can arm the system, check for power and health, and configure the UGS for any unique local factors, such as field of view, positional information, and operating mode. Standardizing this test connection would release the operator from unique hardware requirements for each type of emplaced sensor, save time, and reduce personnel risks.

RF link. An alternate solution with less personnel risk could incorporate an RF or IR communications link for health and status checks. The direct connection may not have a radiated signature, but a low-power RF link may suffice for UGS maintenance checks while simultaneously reducing operator exposure.

Uni- or bi-directional communications. The communications mode for a particular UGS system depends upon each application. For example, one system may only require power to begin operating with no need for remote control. Another more complex system may require remote configuration and triggering to function properly. In either case, standardizing communications protocols increases interoperability and reduces the cost and schedule impacts of unique solutions.

5. DOD DIRECTION

The Deputy Under Secretary of Defense (DUSD) for Technical Collection and Analysis (TC&A) in 2009 tasked the Director, Defense Intelligence Agency, to lead an effort to standardize the UGS user and acquisition communities⁹. This guidance helps minimize duplication of capabilities while encouraging UGS system flexibility for joint operations. In addition, it addresses mission needs while reducing costs by allowing competition between vendors without constraining innovation.

5.1 Flexibility

Acquisition competition. Current UGS developers can use vendor proprietary designs that may impact the warfighter's logistics chain and slow sensor upgrades that increase capabilities¹⁰. Establishing key interface standards with well-defined common protocols could encourage increased UGS vendor participation by leveling the acquisition field. In addition, common protocols could also allow multiple vendor systems to communicate with each other. Better communication between these disparate systems could then enable detection suites that are more robust and more effective than those currently employed.

Mission dynamics. Multiple services and intelligence agencies must coordinate and consolidate their UGS resources in a budget-constrained environment. Battlefield dynamics, however, may drive commanders to tailor their assets toward specific missions. Focusing current and future UGS development on integrated operation without proprietary designs can satisfy both objectives by increasing UGS interoperability and agility.

5.2 Logistics and Maintainability

Use commercial standards. Using commercial standards could ease the adoption of UGS guidelines in the acquisition and development communities. These uniform guidelines could sharply focus the acquisition community on the logistics and maintainability aspects of UGS. For example, using flexible, reconfigurable power supplies might limit multiple power supply variations, subsequently reducing logistics and maintenance costs. Standard connections, cases, and other mechanical features also reduce training costs and increase system re-use.

Minimize unique, vendor proprietary solutions. Unique, vendor proprietary design features decrease flexibility, degrade maintainability over time, and accelerate system obsolescence. Standard design features that can adapt as industry changes would equally benefit vendors and the government. In a similar vein, inputs from the vendor community that help shape standards in the UGS development process increase stakeholder participation and minimize unique solutions.

5.3 Cost

Minimize duplication. Each organization involved in UGS development determines specific performance requirements based upon relevant mission needs. These mission needs, however, may not fully take into account the force mix inherent in joint warfare. Joint UGS development efforts, though well intended, may fail if stakeholders do not modify unique capability needs that defeat design commonality. Accepted common designs enable interoperable UGS systems while minimizing expensive, overlapping capabilities.

Improve commonality of components. Focusing on common UGS components as the building blocks of UGS systems facilitates the development of low-cost, standard, reusable interfaces. This approach could permit an increased emphasis on improving detectors by not using scarce funds to reinvent interconnections with each new generation of UGS systems.

Accelerate development and acquisition. Current CENTCOM operations in the Middle East highlight an enemy that rapidly adapts to our advanced technology systems¹¹. With this adaptability in mind, legacy acquisition processes allow too much time between concept development and capabilities fielded. Standardizing interfaces and protocols to keep developments agile and shorten the acquisition cycle speeds delivery of capabilities to the warfighter while reducing costs.

6. STANDARDIZATION

6.1 Interfaces

Interface standards constitute minimum hardware and software requirements. UGS vendors should not view standards as an overarching constraint on development. Rather, standards define the minimum common features of interfaces, thus allowing multiple systems to share these interfaces.

Mission requirements drive interoperability. Dynamic field operations determine mission requirements, and these requirements drive interoperability. Non-interoperability restricts data flow, multiplies technology risks, and degrades military applications¹². These three factors work together to minimize chances for mission success. Therefore, standards-based UGS interoperability increase the likelihood of operational success.

Plug-and-play success depends upon early specification in the acquisition cycle. A UGS controller with plug-and-play interfaces depends upon well-defined data standards. These clearly specified data standards start with the UGS program offices involving the vendor community early in the acquisition process. The Sensor Web Enablement (SWE) initiative within the Open Geospatial Consortium, Inc.[®] (OGC) serves as an exemplar for early standards development interaction between users and vendors. The SWE initiative focuses on developing standards that enable sensor discovery, tasking, and observations¹³. This effort may serve as a useful paradigm to develop plug-and-play interfaces for UGS controllers.

6.2 Membership

DIA action to lead. In 2009, the DUSD(TC&A) directed the DIA to form and lead a working group that will establish standards for current and future UGS systems. DIA has reached out to DoD and Intelligence Community (IC) members involved with UGS development to participate in the UGS Standards Working Group (SWG). DIA does not intend to reinvent or usurp existing standards, but to identify the needs and gaps. The OGC is pioneering standards in the areas of multiple-sensor discovery and sensor tasking by users. The UGS community will expand upon the work of the OGC while filling in relevant standards gaps.

Army, Air Force, USMC, OGC, NIST, and NASIC. Key members of the UGS SWG include the Army Research Lab (ARL), OGC, the National Institute of Standards and Technology (NIST), the National Air and Space Intelligence Center (NASIC), and the United States Marine Corps (USMC). The SWG will meet regularly throughout the year to work with the UGS acquisition community in developing interoperable systems. The UGS SWG is organizing and developing the technical working groups needed to study and recommend standards for adoption.

7. CONCLUSION

Standards working group. The UGS Standards Working Group has met four times over the past 18 months and has begun defining key interfaces. Work with NIST and NASIC supports the initial development of the UGS controller segment. More work is needed to obtain buy-in by the acquisition program offices. As the SWG defines cooperative interchanges of sensor and control data between multiple sensors operational scenarios, members will highlight gaps in the interface standards to help focus the working group on necessary refinements or modifications.

Open architecture has potential for significant payoffs. With a renewed emphasis on interoperability of multi-phenomenology sensors, and development of common remote ground control systems, the ability to maintain persistence over the area of interest will yield greater situational awareness. Technologies that characterize targets of interest in multiple operating modes (i.e., mobile, at rest, powered, or dormant) can synergistically combine to provide a coherent picture. This picture can only be achieved through sufficient definition of target dynamics, collection environments, and sensor performance. Working closely with field operators, analysts, sensor developers, and acquisition professionals to fully characterize the mission dynamics for an integrated sensor network will enable this vision for future operations.

Terra Harvest future for common standards-driven UGS. DIA is actively pursuing research on an integrated battlefield UGS architecture that will employ multiple, flexible sensors using standards-based development. The Terra Harvest program breaks apart the UGS system into its fundamental components and standardizes the internal and external interfaces to achieve greater interoperability. Following this example, other programs can join the effort, meet

their particular mission requirements, and take advantage of Terra Harvest resources. Terra Harvest will synergize the UGS community, reduce costs, and provide a technology insertion path for next generation sensors.

8. REFERENCES

- [1] Salvatori, J. B., Deputy Under Secretary of Defense for Technical Collection and Analysis, Memorandum for See Distribution: Establishment of Unattended Ground Sensors Working Group, January 5, 2009.
- [2] http://www.pcmag.com/encyclopedia_term/0,2542,t=plug+and+play&i=49389,00.asp
- [3] Bobier, K., Wells, J., and Dapper, M., "Enhanced unattended ground sensor system communications," Proc. IEEE Military Communications Conference (MILCOM-02) IEEE vol 1, 282-289 (2002).
- [4] <http://www.omega.com/temperature/z/OverviewIEEE.html>
- [5] http://www.dodsbir.net/Sitis/archives_display_topic.asp?Bookmark=28092
- [6] Cook, W.R., "On understanding data abstraction, revisited," OOPSLA, October 25-29, 2009, Orlando, FL, USA.
- [7] <http://online.wsj.com/article/SB126102247889095011.html>
- [8] Bobier, K., Wells, J., and Dapper, M., "Enhanced unattended ground sensor system communications," Proc. IEEE Military Communications Conference (MILCOM-02) IEEE Military Communications Conference (MILCOM-02) IEEE vol 1, 282-289 (2002).
- [9] Salvatori, J. B., Deputy Under Secretary of Defense for Technical Collection and Analysis, Memorandum for See Distribution: Establishment of Unattended Ground Sensors Working Group, January 5, 2009.
- [10] Stolovy, G.H., "Common command-and-control user interface for current force UGS," Proc. SPIE 7333, 73331C-73331C-10 (2009) doi:10.1117/12.822186PSISDG00733300000173331C000001.
- [11] Anderson, F., "Adaptive, responsive, and speedy acquisitions," Defense AT&L, FindArticles.com, Jan-Feb, 2010, http://findarticles.com/p/articles/mi_m0QMG/is_1_39/ai_n49416134/
- [12] Reichardt, M., "The havoc of non-interoperability," An Open GIS Consortium (OGC) White Paper, December 10, 2004.
- [13] Botts, M., Percivall, G., Reed, C., and Davidson, J., "OGC[®] sensor web enablement: overview and high level architecture (OGC 07-165)," An OGC White Paper, December 28, 2007.
- [14] Salvatori, J. B., Deputy Under Secretary of Defense for Technical Collection and Analysis, Memorandum for See Distribution: Establishment of Unattended Ground Sensors Working Group, January 5, 2009.